



## SPACE 6

### Technical specification

	Description	Features
EXTERIOR	Width cm/in, Height cm/in, Depth cm/in	240/94, 229/90, 362/143
INTERIOR	Width cm/in, Height cm/in, Depth cm/in	220/87, 205/81, 356/140
WEIGHT	kg/lb	1730/3814
WEIGHT WITH CRATE	kg/lb	2120/4674
GLASS	Acoustic laminated Sound Control glass	Sound insulation Rw 40 dB STC 40
DOOR	Acoustic laminated Sound Control safety glass	Sound insulation Rw 37 dB STC 37
SOLID WALLS	Sandwich element of birch plywood, recycled acoustic EchoFree panel	Sound insulation Rw 49 dB STC 49 Acoustic absorption Class A
ROOF	Sandwich element of birch plywood, recycled acoustic foam and "recycled polyester wool panel"	Sound insulation Rw 45 dB STC 45 Acoustic absorption Class A
FLOOR	Sandwich element of birch plywood, acoustic wool	Acoustic absorption Class B
CARPET	Antistatic and stain resistant low loop pile carpet for public spaces, EN 1307	Excellent acoustics 24dB
ACOUSTIC SURFACES	Acoustic EchoFree panel	Excellent sound absorption capabilities, Class A
AIR VENTILATION	Low consumption air circulation system	Air circulation speed is more than 185 l/s
FURNITURE	Optional	Different sets are available
CONNECTIONS	AC outlet(100-240V) + USB power (optional) Lan cord (optional) Power cord with socket	The availability of connections depends on the market
LIGHTING	LED lighting	Low consumption
CASTERS	For easy relocation	Hidden. Can be activated any time
ADJUSTABLE LEGS	For levelling	Levelling from inside the booth

