



SPACE 4

Technical specification

	Description	Features
EXTERIOR	Width x Height x Depth (cm / in)	240x229x242 / 94x90x95
INTERIOR	Width x Height x Depth (cm / in)	220x205x236 / 87x81x93
WEIGHT	kg / lb	1200 / 2646
WEIGHT WITH CRATE	kg / lb	1460 / 3219
SOUND INSULATION	Airborne sound insulation R' _w =41 dB	Measurements based on ISO 16283-1
EXTERIOR	Laminated exterior panels and cover trims	Medical grade antibacterial laminate
GLASS	Sound Control laminated glass	Sound insulation STC 40 dB
SOLID ELEMENTS	EchoFree panel - sandwich element of birch plywood, ecological foam and acoustic felt	Sound insulation STC 49 dB Acoustic absorption class A
ROOF	EchoFree panel - sandwich element of birch plywood, ecological foam and acoustic felt	Sound insulation STC 45 dB Acoustic absorption Class A
FLOOR	Sandwich element of birch plywood, acoustic wool	Acoustic absorption Class B
CARPET	Antistatic and stain resistant low loop pile carpet for public spaces, EN 1307	Flammability B _{fl} -s1
DOOR HANDEDNESS	Right- or left-handed door	Door handedness can be chosen
FURNITURE	Optional	Different sets are available
AIR VENTILATION	Low consumption air circulation system (stand by 6,8W; in operation 13,6W)	Air circulation speed is more than 125 l/s
CONNECTIONS	AC outlet(100-240V) + USB A (optional) Ethernet port (optional) Power cord length 5 m	The availability of connections depends on the region
LIGHTING	LED lighting (56 W, 4000 K, 900 lm)	Low consumption, energy-efficient
CASTERS	For easy relocation	Hidden. Can be activated any time
ADJUSTABLE LEGS	For levelling	Levelling from inside the booth
INDOOR AIR QUALITY	Indoor Advantage™ Gold	Indoor Air Quality Certified to SCS-EC10.3-2014 v4.0
GENERAL SAFETY	UL 962 listed	Standard for Safety for Household and Commercial Furnishings

